



REVISIONS				
C/L	DESCRIPTION	BY	APP'D	DATE
F	REVISED SPEC FORMAT/ADDED INFO.	MC	AD	03/22/99
G	REMOVED 3-TURN POT REF.	MC	AD	04/20/99
H	REMOVED PART NUMBERS	MC	AD	5/12/00

CHART I

DASH No.	RESIST. $\Omega \pm 5\%$	RESOL. %
-501	500	0.05
-102	1,000	0.05
-502	5,000	0.03
-103	10,000	0.02
-203	20,000	0.02

CHART II

RPM	DC VOLT	ma	MOTOR 2488
16	6	10	-51
28	6	24	-52
40	12	12	-51
60	12	28	-52
72	24	16	-51
96	28	16	-51
120	24	36	-52
120	35	16	-51
124	28	40	-52
148	35	50	-52
NO LOAD			

POTENTIOMETER

6. TO OBTAIN TIME FOR 0 TO 100% VOLTAGE:
DIVIDE 10 BY RPM: EXAMPLE $10 \div 40 = .25$ MINUTE.
5. WATTAGE: 2 WATTS AT 25°C.
4. RESOLUTION: SEE CHART I.
3. INDEPENDENT LINEARITY: $\pm 0.25\%$.
2. RESISTANCE: SEE CHART I.
1. 10-TURN WIREWOUND POTENTIOMETER..

PART No. DESIGNATION
H2488-51-103
 ————— RESISTANCE
 ————— MOTOR
 ————— BASIC PART NUMBER

MOTOR

6. TORQUE: 10 DUNCE-INCHES, MINIMUM, AT 6 VOLTS D.C.
5. BREAKAWAY VOLTAGE: 3 VOLTS D.C.
4. SPEED: SEE CHART II.
3. CURRENT: SEE CHART II.
2. VOLTAGE: SEE CHART II.
1. LOW CURRENT GEARHEAD MOTOR.

TOLERANCES UNLESS OTHERWISE SPECIFIED		PRECISION SALES INC. www.precisionsales.com	
FRACTIONS $\pm 1/64$	DECIMALS .XX $\pm .010$.XXX $\pm .005$	P:610-359-1002 F:610-353-1674	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF MAUREY INSTRUMENT CORP AND ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS IN WHOLE OR IN PART WITHOUT PERMISSION			
PART NO.	NEXT ASSY.	DRAWN BY EVA	SCALE 1:1
		APP'D EM	DATE 10/13/89
		H2488	
		H	